

Generatoare Perkins (Optional alte motoare)



importator BRACO MES SRL

MODEL		P15	P23	P33	P50	P66	P71	P88	P110	P150
Grup electrogen										
Putere (Stand by)	kVA (kW)	15(12)	23(18.4)	33(26.4)	50(40)	66(52.8)	71(53)	88(70.4)	110(88)	150(120)
Putere (Prime)	kVA (kW)	13(10.4)	20(16)	30(24)	45(36)	60(48)	60(48)	80(64)	100(80)	135(108)
Factor de putere	cos Ø	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8
Frecventa	Hz	50	50	50	50	50	50	50	50	50
Dimensiuni ; in paranteza sunt trecute cele pentru carcasa de insonorizare										
Latime	mm	900(900)	900(900)	900(900)	900(900)	900(900)	900(900)	1100(1100)	1100(1100)	1200(1200)
Lungime	mm	1450(1850)	1800(2300)	1800(2300)	1800(2300)	1800(2300)	1800(2300)	2100(2800)	2100(2800)	2800(3800)
Inaltime	mm	1370(1450)	1420(1720)	1420(1720)	1420(1720)	1420(1720)	1420(1720)	1650(1830)	1650(1830)	1650(2220)
Motor										
Model		403C-15G	404C-22G	1103A-33G	1103A-33TG1	1103A-33TG2	1104A-44TG1	1104A-44TG2	1104C-44TAG2	1006 TAG
Turatie	rot/min	1500								
Putere maxima	CP	18.1	27.6	41.6	61.2	79.6	87.4	106.1	133	184.5
Nr cilindri		3	4	3	3	3	4	4	4	6
Sistem admisie		natural	natural	turbo						
Regulator turatie		mecanic								electronic
Capacitate cilindrica	litri	1.496	2.216	3.3	3.3	3.3	4.4	4.4	4.4	5.99
Diametru x cursa	mm x mm	84x90	84x100	105x127	105x127	105x127	105x127	105x127	105x127	100x127
Raport compresie		22.5:1	23.3:1	19.25:1	17.25:1	17.25:1	17.25:1	17.25:1	18.2:1	17.0:1
Sistem electric		12VDC								
Consum sarcina 50%	l / h	2.1	2.9	3.9	5.7	7.3	8	9.7	11.2	16.5
Consum sarcina 75%	l / h	2	4	5.4	8.2	10.5	11.2	14	17.1	24.1
Consum sarcina 100%	l / h	2.6	5.4	7.1	10.7	14.1	14.8	18.7	22.6	31.5
Volum rezervor	litri	100	130	130	130	130	130	260	260	530
Alternator										
Marca		MECCALTE								
Tip		sincron								
Tensiune	V	231/400V								
Suprasarcina admisa		10% o ora la un ciclu de 12ore								
Clasa de izotatie		H								
Precizie reglaj tensiune		±1%								